

Artificial Neural Networks and Deep Learning


Keras tutorial - 07/10/2020

Francesco Lattari, PhD student (francesco.lattari@polimi.it)

Artificial Intelligence and Robotics Laboratory



POLITECNICO
MILANO 1863



Input: Values of x over a mini-batch: $\mathcal{B} = \{x_{1..m}\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$


$$\mu_{\mathcal{B}} \leftarrow \frac{1}{m} \sum_{i=1}^m x_i \quad // \text{mini-batch mean}$$


$$\sigma_{\mathcal{B}}^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_{\mathcal{B}}}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}}$$

$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$

Algorithm 1: Batch Normalization
activation x over a mini-batch





Input: Values of x over a mini-batch: $\mathcal{B} = \{x_1 \dots m\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$

$$\mu_{\mathcal{B}} \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$


// mini-batch mean


$$\sigma_{\mathcal{B}}^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_{\mathcal{B}}}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}}$$

$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$

Algorithm 1: Batch Normalization activation x over a mini-batch





Input: Values of x over a mini-batch: $\mathcal{B} = \{x_1 \dots m\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$

$$\mu_{\mathcal{B}} \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$




// mini-batch mean


$$\sigma_{\mathcal{B}}^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_{\mathcal{B}}}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}}$$

$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$

Algorithm 1: Batch Normalization activation x over a mini-batch





Input: Values of x over a mini-batch: $\mathcal{B} = \{x_1 \dots m\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$

$$\mu_{\mathcal{B}} \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$



// mini-batch mean


$$\sigma_{\mathcal{B}}^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_{\mathcal{B}}}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}}$$

$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$

Algorithm 1: Batch Normalization activation x over a mini-batch





Input: Values of x over a mini-batch: $\mathcal{B} = \{x_{1\dots m}\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$






$$\mu_{\mathcal{B}} \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$



$$\sigma_{\mathcal{B}}^2 \leftarrow \frac{1}{m} \sum_i^m (x_i - \mu_{\mathcal{B}})^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_B}{\sqrt{\sigma^2 + \epsilon}}$$


$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$

Algorithm 1: Batch Normalization





0 0 0 0 0 0 0 0 0
1 1 1 1 1 1 1 1 /
2 2 2 2 2 2 2 2 2
3 3 3 3 3 3 3 3 3
4 4 4 4 4 4 4 4 4
5 5 5 5 5 5 5 5 5
6 6 1 6 6 6 6 6 6




Input: Values of x over a mini-batch
Parameters to be learned:
Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$

$$\mu_B \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$


$$\sigma_B^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_B)^2$$



$$\hat{x}_i \leftarrow \frac{x_i - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv \text{BN}_{\gamma, \beta}(x_i)$$



Algorithm 1: Batch Normalization activation x over a mini-batch





0 0 0 0 0 0 0 0 0
1 1 1 1 1 1 1 1 /
2 2 2 2 2 2 2 2 2
3 3 3 3 3 3 3 3 3
4 4 4 4 4 4 4 4 4

$4^2 \times 5^2$

$2^2 \times 3^2$

$1^2 \times 2^2$

$1^2 \times 1^2$



Input: Values of x over a mini-batch
Parameters to be learned:


Output: $\{y_i = BN_{\gamma, \beta}(x_i)\}$

$$\mu_B \leftarrow \frac{1}{m} \sum_{i=1}^m x_i$$

$$\sigma_B^2 \leftarrow \frac{1}{m} \sum_{i=1}^m (x_i - \mu_B)^2$$

$$\hat{x}_i \leftarrow \frac{x_i - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$


$$y_i \leftarrow \gamma \hat{x}_i + \beta \equiv BN_{\gamma, \beta}(x_i)$$




Algorithm 1: Batch Normalization activation x over a mini-batch



- SGD
- Momentum
- NAG
- Adagrad
- Adadelta
- Rmsprop



```
import keras
```




Keras

Being able to go from idea to result with the least possible delay is key to doing good research

<https://keras.io/>

K Keras





```
import tensorflow as tf  
tf.keras
```

Data structure: tf.Tensor

```
import numpy as np  
  
# 3x3 matrix  
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]  
array = np.array(matrix, dtype=np.int32)  
array  
  
array([[1, 2, 3],  
       [4, 5, 6],  
       [7, 8, 9]], dtype=int32)
```



Data structure: tf.Tensor

```
import numpy as np  
  
# 3x3 matrix  
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]  
array = np.array(matrix, dtype=np.int32)  
array  
  
array([[1, 2, 3],  
       [4, 5, 6],  
       [7, 8, 9]], dtype=int32)
```



NumPy

```
import tensorflow as tf  
  
# 3x3 matrix  
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]  
tensor = tf.constant(matrix, dtype=np.int32)  
tensor  
  
<tf.Tensor: id=38, shape=(3, 3), dtype=int32, numpy=  
array([[1, 2, 3],  
       [4, 5, 6],  
       [7, 8, 9]], dtype=int32)>
```



Data structure: tf.Tensor

```
import numpy as np

# 3x3 matrix
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
array = np.array(matrix, dtype=np.int32)
array

array([[1, 2, 3],
       [4, 5, 6],
       [7, 8, 9]], dtype=int32)
```



NumPy

```
import tensorflow as tf

# 3x3 matrix
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
tensor = tf.constant(matrix, dtype=np.int32)
tensor

<tf.Tensor: id=38, shape=(3, 3), dtype=int32, numpy=
array([[1, 2, 3],
       [4, 5, 6],
       [7, 8, 9]], dtype=int32)>
```



```
print("tensor.shape ->", tensor.shape)
print("tensor.ndim ->", tensor.ndim)
print("tensor.dtype ->", tensor.dtype)
print("tensor.device ->\n", tensor.device)

tensor.shape -> (3, 3)
tensor.ndim -> 2
tensor.dtype -> <dtype: 'int32'>
tensor.device ->
    /job:localhost/replica:0/task:0/device:CPU:0
```



```
import numpy as np

# 3x3 matrix
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
array = np.array(matrix, dtype=np.int32)
array

array([[1, 2, 3],
       [4, 5, 6],
       [7, 8, 9]], dtype=int32)
```



```
import tensorflow as tf

# 3x3 matrix
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
tensor = tf.constant(matrix, dtype=np.int32)
tensor

<tf.Tensor: id=38, shape=(3, 3), dtype=int32, numpy=
array([[1, 2, 3],
       [4, 5, 6],
       [7, 8, 9]], dtype=int32)>
```



Create a tensor

- `tf.constant(value, dtype, shape)`
- `tf.zeros(shape, dtype)`
- `tf.ones(shape, dtype)`
- `tf.random`
 - `normal(`
 `shape, mean, stddev, dtype, seed)`
 - `uniform(`
 `shape, minval, maxval, dtype, seed)`
 -
- `tf.range(start, limit, delta, dtype)`
- `tf.convert_to_tensor(value, dtype)`


Operations on tensors - Tensorflow v1

```
import tensorflow as tf
tf.compat.v1.disable_eager_execution()

matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
tensor1 = tf.constant(matrix, dtype=tf.int32)
tensor2 = tf.ones([3, 3], dtype=tf.int32)
out = tensor1 + tensor2

print(tensor1)
print(tensor2)
print(out)
```

```
Tensor("Const:0", shape=(3, 3), dtype=int32)
Tensor("ones:0", shape=(3, 3), dtype=int32)
Tensor("add:0", shape=(3, 3), dtype=int32)
```



```
tensor1.op
tensor2.op
out.op
```

```
<tf.Operation 'Const' type=Const>
<tf.Operation 'ones' type=Const>
<tf.Operation 'add' type=AddV2>
```

Operations on tensors - Tensorflow v1

```
import tensorflow as tf
tf.compat.v1.disable_eager_execution()


matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
tensor1 = tf.constant(matrix, dtype=tf.int32)
tensor2 = tf.ones([3, 3], dtype=tf.int32)
out = tensor1 + tensor2
```

```
print(tensor1)
print(tensor2)
print(out)
```

```
Tensor("Const:0", shape=(3, 3), dtype=int32)
Tensor("ones:0", shape=(3, 3), dtype=int32)
Tensor("add:0", shape=(3, 3), dtype=int32)
```

```
session = tf.compat.v1.Session()
session.run(out)
```

```
array([[ 2,  3,  4],
       [ 5,  6,  7],
       [ 8,  9, 10]], dtype=int32)
```



```
tensor1.op
tensor2.op
out.op
```

```
<tf.Operation 'Const' type=Const>
```

```
<tf.Operation 'ones' type=Const>
```

```
<tf.Operation 'add' type=AddV2>
```

```
import tensorflow as tf          Eager execution

matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
tensor1 = tf.constant(matrix, dtype=tf.int32)
tensor2 = tf.ones([3, 3], dtype=tf.int32)
out = tensor1 + tensor2

print(tensor1)
print(tensor2)
print(out)
```

```
tf.Tensor(
[[1 2 3]
 [4 5 6]
 [7 8 9]], shape=(3, 3), dtype=int32)
tf.Tensor(
[[1 1 1]
 [1 1 1]
 [1 1 1]], shape=(3, 3), dtype=int32)
tf.Tensor(
[[ 2   3   4]
 [ 5   6   7]
 [ 8   9  10]], shape=(3, 3), dtype=int32)
```

- imperative programming environment
 - operations evaluated immediately
- easier debugging
- natural control flow (Python)

Change data type

- `tf.cast(x, dtype)`

`tf.float16` : 16-bit half-precision floating-point.

`tf.int32` : 32-bit signed integer.

`tf.float32` : 32-bit single-precision floating-point.

`tf.int64` : 64-bit signed integer.

`tf.float64` : 64-bit double-precision floating-point.

`tf.bool` : Boolean.

`tf.bfloat16` : 16-bit truncated floating-point.

`tf.string` : String.

`tf.complex64` : 64-bit single-precision complex.

`tf.qint8` : Quantized 8-bit signed integer.

`tf.complex128` : 128-bit double-precision complex.

`tf.quint8` : Quantized 8-bit unsigned integer.

`tf.int8` : 8-bit signed integer.

`tf.qint16` : Quantized 16-bit signed integer.

`tf.uint8` : 8-bit unsigned integer.

`tf.quint16` : Quantized 16-bit unsigned integer.

`tf.uint16` : 16-bit unsigned integer.

`tf.qint32` : Quantized 32-bit signed integer.

`tf.uint32` : 32-bit unsigned integer.

`tf.resource` : Handle to a mutable resource.


`tf.uint64` : 64-bit unsigned integer.

`tf.variant` : Values of arbitrary types.

`tf.int16` : 16-bit signed integer.


Reshape

- `tf.reshape(tensor, shape)`




Reshape

- `tf.expand_dims(input, axis)`



Reshape

- `tf.squeeze(input, axis)`




Math operations

- *, +, -, / operators (element-wise)
- tf.add(x, y) (element-wise)
 - tf.add_n(inputs)
- tf.multiply(x, y) (element-wise)
 - tf.tensordot(a, b, axes) (matrix multiplication)
- tf.abs(x)
- tf.pow(x, y)
- tf.transpose(a, perm, conjugate)
- ...

Module: tf.math

https://www.tensorflow.org/api_docs/python/tf/math

Slicing




Indexing


- pythonic way: “[]”
 - [idx1, idx2, ..., idxN]
 - [start:stop:step]
- `tf.slice(input_, begin, size)`
- using a condition: `tf.gather_nd(params, indices)`
 - `indices = tf.where(condition)`

Operations on tensors - Tensorflow 2.0

Splitting: `tf.split(value, num_or_size_splits, axis)`





Stacking: `tf.concat(values, axis)`



Data



Data Preparation



Class `tf.data.Dataset`

https://www.tensorflow.org/api_docs/python/tf/data/Dataset

- Methods (main)
 - `__iter__()`
 - `batch(batch_size, drop_remainder=False)`
 - `map(map_fn, num_parallel_calls=None)`
 - `filter(predicate)`
 - `shuffle(buffer_size, seed=None, reshuffle_each_iteration=False)`
 - ...

Class `tf.data.Dataset`

https://www.tensorflow.org/api_docs/python/tf/data/Dataset

- Create a Dataset
 - `range(start, stop, step)`
 - `from_tensors(tensors)`
 - `from_tensor_slices(tensors)`
 - ...

tf.keras.datasets

https://www.tensorflow.org/api_docs/python/tf/keras/datasets

- Fashion MNIST
 - 28x28 grayscale images
 - 10 classes:
 1. T-shirt/top
 2. Trouser/pants
 3. Pullover shirt
 4. Dress
 5. Coat
 6. Sandal
 7. Shirt
 8. Sneaker
 9. Bag
 10. Ankle boot




Class tf.keras.layers

https://www.tensorflow.org/api_docs/python/tf/keras/layers

- Classes of basic building blocks
 - e.g., fully-connected layer

```
tf.keras.layers.Dense(  
    units,  
    activation=None,  
    use_bias=True,  
    kernel_initializer='glorot_uniform',  
    bias_initializer='zeros',  
    kernel_regularizer=None,  
    bias_regularizer=None,  
    activity_regularizer=None,  
    kernel_constraint=None,  
    bias_constraint=None,  
    **kwargs,  
)
```




Class tf.keras.layers

https://www.tensorflow.org/api_docs/python/tf/keras/layers

- Classes of basic building blocks
 - e.g., fully-connected layer

```
tf.keras.layers.Dense(  
    units,  
    activation=None,  
    use_bias=True,  
    kernel_initializer='glorot_uniform',  
    bias_initializer='zeros',  
    kernel_regularizer=None,  
    bias_regularizer=None,  
    activity_regularizer=None,  
    kernel_constraint=None,  
    bias_constraint=None,  
    **kwargs,  
)
```



tf.keras.activations

https://www.tensorflow.org/api_docs/python/tf/keras/activations

Class `tf.keras.layers`

https://www.tensorflow.org/api_docs/python/tf/keras/layers

- Classes of basic building blocks
 - e.g., fully-connected layer

```
tf.keras.layers.Dense(  
    units,  
    activation=None,  
    use_bias=True,  
    kernel_initializer='glorot_uniform',  
    bias_initializer='zeros',  
    kernel_regularizer=None,  
    bias_regularizer=None,  
    activity_regularizer=None,  
    kernel_constraint=None,  
    bias_constraint=None,  
    **kwargs,  
)
```




`tf.keras.initializers`

https://www.tensorflow.org/api_docs/python/tf/initializers

Class `tf.keras.Model`


https://www.tensorflow.org/api_docs/python/tf/keras/Model

- Groups multiple layers



Class tf.keras.Model

https://www.tensorflow.org/api_docs/python/tf/keras/Model



- Groups multiple layers
- Create a Model instance (“functional API”):


1. Instantiate keras Input tensor

https://www.tensorflow.org/api_docs/python/tf/keras/Input

```
x = tf.keras.Input(shape, dtype, ...)
```

Class tf.keras.Model

https://www.tensorflow.org/api_docs/python/tf/keras/Model



- Groups multiple layers
- Create a Model instance (“functional API”):

1. Instantiate keras Input tensor

https://www.tensorflow.org/api_docs/python/tf/keras/Input

```
x = tf.keras.Input(shape, dtype, ...)
```

2. Instantiate and chain keras layers

```
layer1 = tf.keras.layers.LAYER_NAME(...)(x)
layer2 = tf.keras.layers.LAYER_NAME(...)(layer1)
....
out = ....
```

Class tf.keras.Model

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- Groups multiple layers
- Create a Model instance (“functional API”):


1. Instantiate keras Input tensor

https://www.tensorflow.org/api_docs/python/tf/keras/Input

```
x = tf.keras.Input(shape, dtype, ...)
```

2. Instantiate and chain keras layers

```
layer1 = tf.keras.layers.LAYER_NAME(...)(x)
layer2 = tf.keras.layers.LAYER_NAME(...)(layer1)
...
out = ....
```



3. Instantiate Model

```
model = tf.keras.Model(inputs=x, outputs=out)
```

Class tf.keras.Model

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- Groups multiple layers
- Create a Model instance (“functional API”):


1. Instantiate keras Input tensor

https://www.tensorflow.org/api_docs/python/tf/keras/Input

```
x = tf.keras.Input(shape, dtype, ...)
```

2. Instantiate and chain keras layers

```
layer1 = tf.keras.layers.LAYER_NAME(...)(x)
layer2 = tf.keras.layers.LAYER_NAME(...)(layer1)
....
out = ....
```




3. Instantiate Model

```
model = tf.keras.Model(inputs=x, outputs=out)
```

OR...

Class tf.keras.Sequential

https://www.tensorflow.org/api_docs/python/tf/keras/Sequential



- Stacks multiple layers
- Create a Sequential instance (“functional API”):
 - 2 modalities:
 1. model = tf.keras.Sequential([layer1, layer2, ..., layerN])
 2. model = tf.keras.Sequential()
model.add(layer1)
model.add(layer2)
....
model.add(layerN)

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods
 1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods

1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

`tf.keras.optimizers`

https://www.tensorflow.org/api_docs/python/tf/keras/optimizers

- class SGD
- class Adam
- class Adadelta
- ...

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods
 1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

`tf.keras.losses`

https://www.tensorflow.org/api_docs/python/tf/keras/losses

- class `BinaryCrossEntropy`
- class `CategoricalCrossEntropy`
- class `MeanSquaredError`
- ...

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods

1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

`tf.keras.metrics`

https://www.tensorflow.org/api_docs/python/tf/keras/metrics

- class Accuracy
- class MeanIoU
- class Precision
- class Recall
- ...

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods

1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

2. Training model

```
model.fit(  
    x=None,  
    y=None,  
    batch_size=None,  
    epochs=1,  
    verbose=1,  
    callbacks=None,  
    validation_split=0.0,  
    validation_data=None,  
    shuffle=True,  
    class_weight=None,  
    sample_weight=None,  
    initial_epoch=0,  
    steps_per_epoch=None,  
    validation_steps=None,  
    validation_freq=1,  
    max_queue_size=10,  
    workers=1,  
    use_multiprocessing=False,  
    **kwargs)
```

Class `tf.keras.Model`

https://www.tensorflow.org/api_docs/python/tf/keras/Model

- 2 main steps through class methods

1. Prepare model for training

```
model.compile(  
    optimizer='rmsprop',  
    loss=None,  
    metrics=None,  
    loss_weights=None,  
    sample_weight_mode=None,  
    weighted_metrics=None,  
    target_tensors=None,  
    distribute=None,  
    **kwargs)
```

2. Training model

```
model.fit(  
    x=None,  
    y=None,  
    batch_size=None,  
    epochs=1,  
    verbose=1,  
    callbacks=None,  
    validation_split=0.0,  
    validation_data=None,  
    shuffle=True,  
    class_weight=None,  
    sample_weight=None,  
    initial_epoch=0,  
    steps_per_epoch=None,  
    validation_steps=None,  
    validation_freq=1,  
    max_queue_size=10,  
    workers=1,  
    use_multiprocessing=False,  
    **kwargs)
```

Returns a History object containing a record of loss and metric values at each epoch